

Wheelchair platform scale KERN MWB



PROFESSIONAL CARE



Compact wheelchair platform scale with two integrated access ramps for easy access

Features

- Especially suitable for weighing patients in wheelchairs, because the low-profile platform can be approached from either side
- **1** The large steel weighing plate also makes it ideal for weighing obese patients
- Ideal also for rapid weighing of, e.g. for rapid weighing of e.g. laundry carts, container trolleys, roller containers, etc.
- Secure and non-slip positioning with height-adjustable rubber feet
- **2** Level indicator to level the balance precisely
- Hold function:
When patients do not stand or sit completely still, a stable weight is calculated using an average weight and this is then "frozen". This means that you have sufficient time to attend to the patient first and then take the weight reading in peace
- BMI function to determine underweight/normal weight/surplus weight
- **3** The scale can be easily transported using the two handles and two rollers and does not require much storage space
- Wall mount for the display device
- Protective working cover included with delivery

Technical data

- Large backlit LCD display, digit height 25 mm
- Dimensions of display device W×D×H 200×130×60 mm
- Overall dimensions, W×D×H 1050×1050×100 mm
- Batteries included, 6×1,5 V AA, operating time up to 40 h
- Cable length of display device approx. 300 cm
- Net weight approx. 55 kg

Accessories

- Protective working cover over the display device, scope of delivery: 5 items, KERN MBC-A06S05
- Cleaning cloths, alcohol-free cloths for wipe disinfectant. Fulfill the legal requirements for occupational safety in accordance with TRGS 525/540. Packaging contents 80 pcs., size 20×22 cm per cloth, KERN MYC-01
- For more details see the internet

STANDARD



| Model | Weighing range | Readability | Weighing surface | |
|------------|----------------|-------------|------------------|--|
| KERN | [Max] kg | [d] kg | mm | |
| MWB 300K-1 | 300 | 0,1 | 800×800 | |

Pictograms

| | | |
|--|---|---|
| <p>Adjusting program CAL: For quick setting up of the balance's accuracy. External adjusting weight required.</p> | <p>ZERO: Resets the display to "0"</p> | <p>360° rotatable microscope head</p> |
| <p>Memory: Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.</p> | <p>Hold function: When patients do not stand, sit or lie completely still, a stable weight is calculated using an average weight</p> | <p>Monocular Microscope: For the inspection with one eye.</p> |
| <p>Data interface RS-232: To connect the balance to a printer, PC or network</p> | <p>Hold function: When the weighing conditions are unstable, a stable weight is calculated as an average value.</p> | <p>Binocular Microscope: For the inspection with both eyes</p> |
| <p>RS-485 data interface: To connect the balance to a printer, PC or other peripherals. Suitable for data transfer over large distances. Network in bus topology is possible</p> | <p>Protection against dust and water splashes IPxx: The type of protection is shown in the pictogram.</p> | <p>Trinocular Microscope: For the inspection with both eyes and the additional option for the connection of a camera</p> |
| <p>KERN Communication Protocol (KCP): It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems</p> | <p>Stainless steel: The balance is protected against corrosion.</p> | <p>Abbe Condenser: With high numerical aperture for the concentration and the focusing of light.</p> |
| <p>Bluetooth® data interface: To transfer data from the balance to a printer, PC or other peripherals</p> | <p>Suspended weighing: Load support with hook on the underside of the balance.</p> | <p>Halogen illumination: For pictures bright and rich in contrast.</p> |
| <p>Control outputs (optocoupler, digital I/O): To connect relays, signal lamps, valves, etc.</p> | <p>Battery operation: Ready for battery operation. The battery type is specified for each device.</p> | <p>LED illumination: Cold, energy saving and especially long-life illumination.</p> |
| <p>Statistics: using the saved values, the device calculates statistical data, such as average value, standard deviation etc.</p> | <p>Rechargeable battery pack: Rechargeable set.</p> | <p>Fluorescence illumination for compound microscopes: With 100W mercury lamp and filter.</p> |
| <p>PC Software: to transfer the measurements from the device to a PC</p> | <p>Battery operation rechargeable: Prepared for a rechargeable battery operation</p> | <p>Fluorescence illumination for compound microscopes: With 3 W LED illumination and filter.</p> |
| <p>GLP/ISO-Protokoll: With date and time. Only with KERN printers</p> | <p>Universal mains adapter: with universal input and optional input socket adapters for A) EU, CH B) EU, CH, GB, USA</p> | <p>Phase contrast unit: For a higher contrast.</p> |
| <p>Piece counting: Reference quantities selectable. Display can be switched from piece to weight</p> | <p>Mains adapter: 230V/50Hz in standard version for EU. On request GB, AUS or USA version available.</p> | <p>Darkfield condenser/unit: For a higher contrast due to indirect illumination</p> |
| <p>Totalising level A: The weights of similar items can be added together and the total can be printed out.</p> | <p>Power supply: Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, AUS or USA on request.</p> | <p>Polarising unit: To polarise the light.</p> |
| <p>Weighing units: Can be switched to e.g. nonmetric units at the touch of a key. Please refer to website for more details</p> | <p>Weighing principle: Strain gauges Electrical resistor on an elastic deforming body.</p> | <p>Infinity system: Infinity corrected optical system.</p> |
| <p>Weighing with tolerance range: (Check weighing) Upper and lower limiting can be programmed individually, e.g. for sorting and dosing. The process is supported by an audible or visual signal, see the relevant model</p> | <p>Peak hold function: capturing a peak value within a measuring process.</p> | <p>Automatic temperature compensation: For measurements between 10 °C and 30 °C</p> |
| | <p>Push and Pull: the measuring device can capture tension and compression forces.</p> | <p>Verification possible: The time required for verification is specified in the pictogram.</p> |
| | <p>Integrated scale: In the eyepiece.</p> | <p>Package shipment: The time required for internal shipping preparations is shown in days in the pictogram.</p> |
| | | <p>Pallet shipment: The time required for internal shipping preparations is shown in days in the pictogram.</p> |

*The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by KERN & SOHN GmbH is under license. Other trademarks and trade names are those of their respective owners.

Your KERN specialist dealer